

# Toyana GW 070 plain bearings

Advance Toyana GW 070 plain bearings is your 40 mm da source for quality and accessories. shop online 36.5 mm dc for home delivery or pick up in one of our 10000 .

da	40 mm
db	49.2 mm
dc	36.5 mm
Da	90 mm
Ca	42.799 mm
A1	60.325 mm
A2	172.244 mm
S	4.763 mm
ba	29.369 mm
H	125.412 mm
H1	63.5 mm
H2	25.4 mm
J min.	165.1 mm
J max.	177.8 mm
L	209.55 mm
N1	15.875 mm
R1	31.75 mm
R2	15.875 mm
RG	1/8 NPT
PG	1/8 NPT
h	30.163 mm
Housing	SAF 308
Bearing	22308 E

Lock nut	N 08
Lock washer	W 08
Stabilizing ring	SR-10-8
Taconite seal (db shaft position)	TER 24
Taconite seal (dc shaft position)	TER 17
End plug (suffix Y)	EPR 3
Max. speed for Taconite seal	1575 r/min
P60°	32.5 kN
P90°	19.6 kN
P120°	12.5 kN
P150°	11.1 kN
P180°	13.8 kN
Pa	8.9 kN
Mass pillow block	7.01 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.5 in
Initial grease fill	31.185 g