

Toyana HK0508 cylindrical roller bearings

Enjoy High Margins on Competitive 35 Outer Diameter (mm) Pricing.Great Wholesale Products at 80x35x22.75 Size (mm) Low Costs. 80 Bore Diameter (mm)

Size (mm)	80x35x22.75
Bore Diameter (mm)	80
Outer Diameter (mm)	35
Width (mm)	22,75
d	35 mm
D	80 mm
T	22.75 mm
d1	54.55 mm
B	21 mm
C	18 mm
r1,2 – min.	2 mm
r3,4 – min.	1.5 mm
a	16 mm
da – max.	46 mm
db – min.	44.5 mm
Da – min.	70 mm
Da – max.	72.5 mm
Db – min.	74 mm
Ca – min.	3 mm
Cb – min.	4.5 mm
ra – max.	2 mm
rb – max.	1.5 mm

Basic dynamic load rating – C	72.1 kN
Basic static load rating – C0	73.5 kN
Fatigue load limit – Pu	8.3 kN
Reference speed	6700 r/min
Limiting speed	9000 r/min
Calculation factor – e	0.31
Calculation factor – Y	1.9
Calculation factor – Y0	1.1
Inventory	15.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.529
EAN	7316577748881
Product Group	B04334
bore diameter:	35 mm
operating temperature range:	Maximum of +250 °F
cup width:	18 mm
dynamic load capacity:	72.1 kN
assembly type:	Cone & Cup
static load capacity:	73.5 kN
outside diameter:	80 mm
finish/coating:	Uncoated
cone width:	21 mm
maximum rpm:	9000 RPM
closure type:	Open
series:	303
cage material:	Steel
flange type:	Non-Flanged Cup