

# Toyana N313 E cylindrical roller bearings

LET OUR Toyana N313 E cylindrical roller bearings EXPERTS GET YOU THE PARTS 0.0 Inventory YOU NEED.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.264   |
| EAN                       | 0883450035118   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22213   |
| Seals                     | Double Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>65MM Bore; 165MM Bolt Circle;<br>117MM Bolt Spacing; 1 Piece<br>Solid; Conc |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Collar   With Set Screw |
| UNSPSC                             | 31171501                                    |
| Harmonized Tariff Code             | 8483.20.40.80                               |
| Noun                               | Bearing                                     |
| Keyword String                     | Flanged                                     |
| Weight / LBS                       | 16  |
| D                                  | 3.39 Inch   86.1 Millimeter                 |
| Nominal Bolt Circle Diameter Round | 6.5 Inch   165 Millimeter                   |
| Bolt Spacing                       | 4.6 Inch   117 Millimeter                   |
| d                                  | 2.559 Inch   65 Millimeter                  |
| Cartridge Pilot Diameter           | 5.512 Inch   140 Millimeter                 |
| Cartridge Pilot Depth              | 1.125 Inch   28.575 Millimeter              |