## Toyana NF264 E cylindrical roller bearings

Shop Toyana NF264 E cylindrical roller bearings huge online discount 0.0 Inventory inventory. and Import machinery parts your car TIMKEN Manufacturer Name needs with Free Shipping and Free Extended Warranty.

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | TIMKEN                                      |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 25.878                                      |
| EAN                       | 0883450300308                               |
| Product Group             | M06288                                      |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar                           |
| Housing Style             | 4 Bolt Pillow Block                         |
| Rolling Element           | Spherical Roller Bearing                    |
| Housing Material          | Cast Steel                                  |
| Expansion / Non-expansion | Expansion                                   |
| Mounting Bolts            | 3/4 Inch                                    |
| Relubricatable            | Yes   |
| Insert Part Number        | 22220                                       |
| Seals                     | Teflon Labyrinth                            |
| Housing Configuration     | 1 Piece Solid                               |
| Inch — Metric             | Metric                                      |
| Other Features            | Double Row   Single Collar   With Set Screw |

| Long Description                 | 4 Bolt Pillow Block; 100MM Bore;<br>108MM Base to Center Height;<br>Concentric Collar Mount;<br>Spherical Rol |
|----------------------------------|---|
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Weight / LBS                     | 57  |
| В                                | 4.252 Inch   108 Millimeter   |
| D                                | 4.59 Inch   116.586 Millimeter  |
| Nominal Bolt Center to<br>Center | 12.1 Inch   308.5 Millimeter  |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter  |
| Bolt Spacing Minimum             | 10.875 Inch   276.225Millimeter   |
| Bolt Spacing Maximum             | 13.38 Inch   339.852Millimeter  |
| d                                | 3.937 Inch   100 Millimeter   |