

Toyana NJ2220 E cylindrical roller bearings

offers 150 Bore Diameter (mm) a Toyana NJ2220 E cylindrical roller bearings selection of Genuine at Wholesale Prices. We 150x225x90 Size (mm) are 225 Outer Diameter (mm) a Toyana NJ2220 E cylindrical roller bearings Certified Parts Retailer

Size (mm)	150x225x90
Bore Diameter (mm)	150
Outer Diameter (mm)	225
Width (mm)	90
d	150 mm
D	225 mm
H	90 mm
d1	193.7 mm
2C	45 mm
r1,2 – min.	2.1 mm
r3,4 – min.	1 mm
da – min.	178 mm
Da – min.	212.4 mm
Da – max.	213 mm
ra – max.	2 mm
rb – max.	1 mm
Basic dynamic load rating – C	127 kN
Basic static load rating – C0	440 kN
Fatigue load limit – Pu	15.3 kN
Limiting speed for grease lubrication	3000 r/min

Limiting speed for oil lubrication	3600 mm/min
Preload	1015 N
Static Axial rigidity	1125 N/micron
Gref	55.8 cm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	7316575042684
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 5 ISO P5
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	60 Degree
Raceway Style	Not Applicable
Cage Material	Brass
Rolling Element	Ball Bearing
Flush Ground	No
Inch – Metric	Metric
Other Features	Double Row Angular Contact Thrust Bearing Double Direction
Long Description	150MM Bore; 225MM Outside Diameter; 90MM Width; Open Enclosure; ABEC 5 ISO P5 Precision; Steel Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28

Noun	Bearing
Keyword 3	Thrust
Keyword String	Ball Angular Contact Thrust
Weight / LBS	23.14851
Width	3.543 Inch 90 Millimeter
Bore	5.906 Inch 150 Millimeter
Outside Diameter	8.858 Inch 225 Millimeter
r1,2 min.	2.1 mm
r3,4 min.	1 mm
da min.	178 mm
Da min.	212.4 mm
Da max.	213 mm
ra max.	2 mm
rb max.	1 mm
Basic dynamic load rating C	127 kN
Basic static load rating C0	440 kN
Fatigue load limit Pu	15.3 kN
Attainable speed for grease lubrication	3000 r/min
Attainable speed for oil-air lubrication	3600 r/min
Static axial stiffness	1125 N/ μ m
Reference grease quantity Gref	55.8 cm ³
Mass bearing	10.6 kg