Toyana NJ228 E cylindrical roller bearings

Enjoy High Margins on Competitive Pricing.Great 2.9375 in d Wholesale Products at Low Costs.

d2.9375 inbase width:5 inoverall length:13.0000 inexpansion type:Expansion Bearing (Floating)overall height:7.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000D9-3/4 in		
overall length:13.0000 inexpansion type:Expansion Bearing (Floating)overall height:7.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing device:Double Concentric Collarseries:5000	d	2.9375 in
expansion type:Expansion Bearing (Floating)overall height:7.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000	base width:	5 in
overall height:7.3125 infinish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	overall length:	13.0000 in
finish/coating:Powder Coatedmounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Double Concentric Collarseries:5000	expansion type:	Expansion Bearing (Floating)
mounting:Four-Bolt BaseB4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	overall height:	7.3125 in
B4-7/8 inbearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	finish/coating:	Powder Coated
bearing type:Spherical Rollerseal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	mounting:	Four-Bolt Base
seal type:Contact/Lipbore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	В	4-7/8 in
bore type:Roundradial dynamic load capacity:46800 lbhousing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:5000	bearing type:	Spherical Roller
radial dynamic load capacity: 46800 lb housing construction: Solid Pillow Block radial static load capacity: 55700 lb base to bore centerline: 3.5000 in maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000	seal type:	Contact/Lip
housing construction:Solid Pillow Blockradial static load capacity:55700 lbbase to bore centerline:3.5000 inmaximum rpm:1700 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000	bore type:	Round
radial static load capacity: 55700 lb base to bore centerline: 3.5000 in maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000	radial dynamic load capacity:	46800 lb
base to bore centerline: 3.5000 in maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000	housing construction:	Solid Pillow Block
<pre>maximum rpm: 1700 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Double Concentric Collar series: 5000</pre>	radial static load capacity:	55700 lb
housing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000	base to bore centerline:	3.5000 in
lubrication type:Lubrication Fittinglocking device:Double Concentric Collarseries:5000	maximum rpm:	1700 RPM
locking device: Double Concentric Collar series: 5000	housing material:	Cast Iron
series: 5000	lubrication type:	Lubrication Fitting
	locking device:	Double Concentric Collar
D 9-3/4 in	series:	5000
	D	9-3/4 in
standards met: ANSI/ABMA STD 9-1990	standards met:	ANSI/ABMA STD 9-1990