

Toyana NJ306 E cylindrical roller bearings

What is the 7 mm B best place 50 mm d to buy Toyana NJ306 E cylindrical roller bearings 65 mm D online? Manufacturing Service .

d	50 mm
D	65 mm
B	7 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.05 kg
Dynamic load, C	6.6 kN
Static load, C ₀	6.1 kN
Fatigue limit load, C _u	0.28 kN
f ₀	16.1
N _{lim} (grease)	9,600 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	14.42 Hz
Characteristic outer ring frequency, BPF ₀	11.17 Hz
Characteristic inner ring frequency, BPFI	12.83 Hz
da min	52 mm
da max	54 mm

Da max	63 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.052
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Riveted Cage
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 65MM Outside Diameter; 7MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.115
Bore	1.969 Inch 50 Millimeter

Outside Diameter	2.559 Inch 65 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter