

Toyana NN4928 K cylindrical roller bearings

Toyana NN4928 K cylindrical roller bearings Product Brochures , Manufacturing 88.9×114.3×50.8 Size (mm) Service . Get Your Free.

Size (mm)	88.9×114.3×50.8
Bore Diameter (mm)	88,9
Outer Diameter (mm)	114,3
Width (mm)	50,8
Fw	88,9 mm
D	114,3 mm
C	50,8 mm
r5 min.	2,03 mm
Weight	1,238 Kg
Basic dynamic load rating (C)	187 kN
Basic static load rating (C0)	375 kN
(Grease) Lubrication Speed	4900 r/min
Inventory	2.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	1.24
EAN	0605790186271
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring
Enclosure	Open

Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Inch
Relubricatable	Yes
Thrust Bearing	No
Long Description	3-1/2" Bore; 4-1/2" Outside Diameter; 2" Width; Needle Roller Bearing; Roller Assembl
Other Features	2 Rib Outer Ring Steel Cage Heavy Duty Oil Hole
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer Item Number	HJ-567232
Weight / LBS	2.73
Width	2 Inch 50.8 Millimeter
Bore	3.5 Inch 88.9 Millimeter
Outside Diameter	4.5 Inch 114.3 Millimeter
Bearing No.	HJ-567232
rs(min)	2.03
Used with inner ring No.	IR-475632
Cr	50.8
C0r	375
Cu	58.9
Grease lub.	3200

Oil lub.	4900
(Refer.)Mass(kg)	1.238
Clearance fit S(h6)(max.)	88.900
Clearance fit S(h6)(min.)	88.877
Clearance fit H(H7)(max.)	114.336
Clearance fit H(H7)(min.)	114.300
Tight transition fit S(f6)(max.)	88.864
Tight transition fit S(f6)(min.)	88.842
Tight transition fit H(N7)(max.)	114.287
Tight transition fit H(N7)(min.)	114.252
Da	104.78