## Toyana NNF5012 V cylindrical roller bearings

Toyana NNF5012 V cylindrical roller bearings SEARCH — Whether it's agriculture or construction equipment your TIMKEN Manufacturer Name working on, Has the you N/A Minimum Buy Quantity need. 0.0 Inventory

| Turrentenni               | 0.0  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 9.988  |
| EAN                       | 0883450250672  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 3" Bore;<br>3-1/4" Base to Center Height;<br>Eccentric Collar Mount; Spheri |

| UNSPSC                           | 31171511                      |
|----------------------------------|-------------------------------|
| Harmonized Tariff Code           | 8483.20.40.80                 |
| Noun                             | Bearing                       |
| Keyword String                   | Pillow Block                  |
| Manufacturer Item Number         | QMPF15J300S0                  |
| Weight / LBS                     | 27                            |
| В                                | 3.25 Inch   82.55 Millimeter  |
| Nominal Bolt Center to<br>Center | 8.4 Inch   213 Millimeter     |
| d                                | 3 Inch   76.2 Millimeter      |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter          |
| D                                | 3.62 Inch   91.948 Millimeter |
| Bolt Spacing Maximum             | 9.1 Inch   231.14Millimeter   |
| Bolt Spacing Minimum             | 7.6 Inch   193.04Millimeter   |