

Toyana NNU4930 V cylindrical roller bearings

How do I place an EMERGENCY 55 Outer Diameter (mm) order for a Toyana NNU4930 V cylindrical roller bearings that I want to pick up at a our 140x55x33 Size (mm) store?

Size (mm)	140x55x33
Bore Diameter (mm)	140
Outer Diameter (mm)	55
Width (mm)	33
d	55 mm
D	140 mm
B	33 mm
D1	109.45 mm
F	77.2 mm
r1,2 – min.	2.1 mm
r3,4 – min.	2.1 mm
s	2.6 mm
da – min.	69 mm
da – max.	74 mm
db – min.	79 mm
Da – max.	126 mm
ra – max.	2 mm
rb – max.	2 mm
Basic dynamic load rating – C	142 kN
Basic static load rating – C0	140 kN
Fatigue load limit – Pu	18.6 kN
Reference speed	5600 r/min

Limiting speed	6300 r/min
Calculation factor – kr	0.15
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.562
EAN	7316577110190
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	55MM Bore; Straight Bore Profile; 140MM Outside Diameter; 33MM Width; Polymer Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing

Manufacturer Item Number	NU 411
Weight / LBS	5.644
Bore	2.165 Inch 55 Millimeter
Width	1.299 Inch 33 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
D1 ≈	109.45 mm
r1,2 min.	2.1 mm
r3,4 min.	2.1 mm
s max.	2.6 mm
da min.	69 mm
da max.	74 mm
db min.	79 mm
Da max.	126 mm
ra max.	2 mm
rb max.	2 mm
Basic dynamic load rating C	142 kN
Basic static load rating C0	140 kN
Fatigue load limit Pu	18.6 kN
Calculation factor kr	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	2.48 kg