## Toyana NU222 E cylindrical roller bearings

QuestionToyana NU222 E cylindrical roller bearings ? Find what 0.0 Inventory you need faster by entering your information .

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 3.13   |
| EAN                       | 0782475772940  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | BRG-UN2-111  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   With Set Screw  |
| Long Description          | 2 Bolt Pillow Block; 1-11/16"<br>Bore; 2-1/8" Base to Center<br>Height; Concentric Collar Mount; |
| UNSPSC                    | 31171511   |

|                                  | 1                              |
|----------------------------------|--------------------------------|
| Harmonized Tariff Code           | 8483.20.40.80                  |
| Noun                             | Bearing                        |
| Keyword String                   | Pillow Block                   |
| Manufacturer Item Number         | P2B-UN2-111E UNI-II            |
| Manufacturer Internal<br>Number  | 048019                         |
| Weight / LBS                     | 6.9                            |
| В                                | 2.125 Inch   53.98 Millimeter  |
| Nominal Bolt Center to<br>Center | 5.5 Inch   140 Millimeter      |
| D                                | 1.906 Inch   48.42 Millimeter  |
| d                                | 1.688 Inch   42.875 Millimeter |
| Bolt Spacing Minimum             | 5.188 Inch   131.775Millimeter |
| Bolt Spacing Maximum             | 5.875 Inch   149.225Millimeter |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter           |