

Toyana NU340 E cylindrical roller bearings

LET OUR 58 Bore Diameter (mm) Toyana NU340 E cylindrical roller bearings EXPERTS GET 58x45x7 Size (mm) YOU 45 Outer Diameter (mm) THE PARTS YOU NEED.

Size (mm)	58x45x7
Bore Diameter (mm)	58
Outer Diameter (mm)	45
Width (mm)	7
d	45 mm
D	58 mm
B	7 mm
d1	49.6 mm
d2	49.6 mm
D1	53.6 mm
r1,2 – min.	0.3 mm
r3,4 – min.	0.15 mm
a	15.5 mm
da – min.	47 mm
db – min.	47 mm
Da – max.	56 mm
Db – max.	57.2 mm
ra – max.	0.3 mm
rb – max.	0.15 mm
dn	50 mm
Basic dynamic load rating – C	4.6 kN
Basic static load rating – C0	5 kN

Fatigue load limit – Pu	0.212 kN
Limiting speed for grease lubrication	20000 r/min
Limiting speed for oil lubrication	30000 mm/min
Ball – Dw	3.175 mm
Ball – z	31
Gref	0.36 cm ³
Calculation factor – e	0.68
Calculation factor – Y2	1.41
Calculation factor – Y0	0.76
Calculation factor – X2	0.67
Calculation factor – Y1	0.92
Preload class A – GA	41 N
Preload class B – GB	125 N
Preload class C – GC	250 N
Calculation factor – f	1.24
Calculation factor – f1	0.97
Calculation factor – f2A	1
Calculation factor – f2B	1.08
Calculation factor – f2C	1.15
Calculation factor – fHC	1
Preload class A	87 N/micron
Preload class B	139 N/micron
Preload class C	189 N/micron
r1,2 min.	0.3 mm
r3,4 min.	0.15 mm
da min.	47 mm
db min.	47 mm
Da max.	56 mm
Db max.	57.2 mm

ra max.	0.3 mm
rb max.	0.15 mm
Basic dynamic load rating C	4.62 kN
Basic static load rating C ₀	5 kN
Fatigue load limit P _u	0.212 kN
Attainable speed for grease lubrication	20000 r/min
Attainable speed for oil-air lubrication	30000 r/min
Ball diameter D _w	3.175 mm
Number of balls z	31
Reference grease quantity G _{ref}	0.36 cm ³
Preload class A GA	41 N
Static axial stiffness, preload class A	87 N/μm
Preload class B GB	125 N
Static axial stiffness, preload class B	139 N/μm
Preload class C GC	250 N
Static axial stiffness, preload class C	189 N/μm
Calculation factor f	1.24
Calculation factor f ₁	0.97
Calculation factor f _{2A}	1
Calculation factor f _{2B}	1.08
Calculation factor f _{2C}	1.15
Calculation factor f _{HC}	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y ₂	0.87
Calculation factor (single, tandem) Y ₀	0.38
Calculation factor (single, tandem) X ₂	0.41
Calculation factor (back-to-back, face-to-face) Y ₁	0.92

Calculation factor (back-to-back, face-to-face) Y2	1.41
Calculation factor (back-to-back, face-to-face) Y0	0.76
Calculation factor (back-to-back, face-to-face) X2	0.67
Mass bearing	0.039 kg