

# Toyana TUP1 22.25 plain bearings

Toyana TUP1 22.25 plain bearings Warehouse offers car parts and car accessories. We sell discount online as Mounted Bearing Engineering Group well as cheap machinery parts.

|                         |                         |
|-------------------------|-------------------------|
| Engineering Group       | Mounted Bearing         |
| Shaft Size              | 50 mm                   |
| Shaft Size Type         | Metric                  |
| Full Timken Part Number | QMFL10J050SB            |
| Locking Style           | Eccentric               |
| Weight                  | 11.0 lb                 |
| Housing Style           | Four-Bolt Square Flange |
| UPC Code                | 0883450069823           |
| Dimension BC            | 5.75 in                 |
| Dimension C             | 2.76 in                 |
| Dimension D             | 4.540 in                |
| Dimension E             | 4.07 in                 |
| Dimension F             | 5.19 in                 |
| Dimension H             | 0.91 in                 |
| Dimension J (Bolt Size) | 0.5 in                  |
| Dimension K             | 0.98 in                 |
| Dimension L Exp         | 3.26 in                 |
| Dimension L Fix         | 3.18 in                 |
| Dimension M             | 1.89 in                 |
| Dimension N             | 2.460 in                |
| Dimension R             | 0.31 in                 |
| Dimension S             | 2.87 in                 |

|                                     |           |
|-------------------------------------|-----------|
| C0 – Static Load                    | 26600 lb  |
| C – Dynamic Load (Basic)            | 26300 lb  |
| e – Geometry Factor                 | 0.25      |
| Y1 – Geometry Factor                | 2.71      |
| Y2 – Geometry Factor                | 4.04      |
| Oil Lubrication – M/N Seal          | 2400 rpm  |
| Oil Lubrication – T Seal            | 4200 rpm  |
| Oil Lubrication – B/C/O Seal        | 1800 rpm  |
| Grease Lubrication – M/N Seal       | 2400 rpm  |
| Grease Lubrication – T Seal         | 3550 rpm  |
| Grease Lubrication – B/C/O Seal     | 1800 rpm  |
| Float                               | 0.050 in  |
| Shaft Tolerance                     | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0016    |
| Eng Internal Radial Clearance – Max | 0.0026    |
| Pre Install Clearance Min           | 0.0016 in |
| Pre Install Clearance Max           | 0.0026 in |