

Toyana TUP1 28.15 plain bearings

170 Million used Toyana TUP1 28.15 plain bearings instantly searchable. Shop our large selection of parts based on brand, price, description, and location. Order the with stock 0.0 Inventory ...

| | |
|------------------------------|--------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 25.593 |
| EAN | 7316577005823 |
| Product Group | B04334 |
| bore diameter: | 220 mm |
| operating temperature range: | Maximum of +300 °F |
| cup width: | 57 mm |
| dynamic load capacity: | 897 kN |
| assembly type: | Cone & Cup |
| static load capacity: | 1660 kN |
| outside diameter: | 340 mm |
| finish/coating: | Uncoated |
| cone width: | 76 mm |
| maximum rpm: | 1700 RPM |
| closure type: | Open |
| series: | 320 |
| cage material: | Steel |
| flange type: | Non-Flanged Cup |
| Dimension series | 4FD |

| | |
|-----------------------------|------------|
| d | 220 mm |
| D | 340 mm |
| T | 76 mm |
| d1 ≈ | 280.88 mm |
| B | 76 mm |
| C | 57 mm |
| r1,2 min. | 4 mm |
| r3,4 min. | 3 mm |
| a | 72.089 mm |
| da max. | 244 mm |
| db min. | 238 mm |
| Da min. | 300 mm |
| Da max. | 325 mm |
| Db min. | 326 mm |
| Ca min. | 12 mm |
| Cb min. | 19 mm |
| ra max. | 4 mm |
| rb max. | 3 mm |
| Basic dynamic load rating C | 955 kN |
| Basic static load rating C0 | 1660 kN |
| Fatigue load limit Pu | 150 kN |
| Reference speed | 1300 r/min |
| Limiting speed | 1700 r/min |
| Calculation factor e | 0.43 |
| Calculation factor Y | 1.4 |
| Calculation factor Y0 | 0.8 |
| Mass bearing | 24.6 kg |