

Toyana TUP1 60.70 plain bearings

Toyana TUP1 60.70 plain bearings 12 Bore Diameter (mm) with easy-to-use parts graphics, giving you the 12x32x10 Size (mm) ability to 32 Outer Diameter (mm) check parts availability, pricing, examine remanufactured options.

| | |
|-------------------------------|------------------|
| Size (mm) | 12x32x10 |
| Bore Diameter (mm) | 12 |
| Outer Diameter (mm) | 32 |
| Width (mm) | 10 |
| d | 12 mm |
| D | 32 mm |
| B | 10 mm |
| C | 10 mm |
| r min. | 0.6 mm |
| Basic dynamic load rating (C) | 6,8 kN |
| Basic static load rating (C0) | 3,05 kN |
| Bore Type | Cylindrical Bore |
| Enclosure | Double Seal |
| Configuration | Single Row |
| Weight | 0.037 kg |
| Bore Size | 12 mm |
| Outside Diameter | 32 mm |
| Width | 10 mm |
| Fillet Radius/Chamfer | 0.6 mm |
| Dynamic Load Rating | 6,800 N |
| Static Load Rating | 3,050 N |

| | |
|-------------------------|-------------------|
| Limiting Speed – Grease | 17,000 rpm |
| Factor f_0 | 12.3 |
| Radial Clearance | 0.003 to 0.018 mm |
| d_a (min) | 17 mm |
| D_a (max) | 27 mm |
| r_a (max) | 0.6 mm |