

# Toyana TUP2 110.60 plain bearings

Toyana TUP2 110.60 plain bearings, Units and Housings CAD models , Manufacturing Service Mounted Bearing Engineering Group . Get Your Free. 60 mm Shaft Size

|                          |                         |
|--------------------------|-------------------------|
| Engineering Group        | Mounted Bearing         |
| Shaft Size               | 60 mm                   |
| Shaft Size Type          | Metric                  |
| Full Timken Part Number  | QVFC15V060SB            |
| Locking Style            | Double V-Lock           |
| Weight                   | 25 lb                   |
| Housing Style            | Four-Bolt Square Flange |
| UPC Code                 | 0883450065443           |
| Dimension BC             | 8.47 in                 |
| Dimension A              | 10.04 in                |
| Dimension C              | 3.7 in                  |
| Dimension D              | 6.690 in                |
| Dimension E              | 6.000 in                |
| Dimension F              | 7.56 in                 |
| Dimension H              | 0.94 in                 |
| Dimension J (Bolt Size)  | 0.625 in                |
| Dimension G              | 1 in                    |
| Dimension L              | 3.43 in                 |
| Dimension N              | 2.550 in                |
| Dimension RVV            | 0.66 in                 |
| Dimension SVV            | 4.09 in                 |
| C – Dynamic Load (Basic) | 49900 lb                |

|                                     |           |
|-------------------------------------|-----------|
| C0 – Static Load                    | 54100 lb  |
| e – Geometry Factor                 | 0.25      |
| Y1 – Geometry Factor                | 2.74      |
| Y2 – Geometry Factor                | 4.08      |
| Oil Lubrication – M/N Seal          | 1600 rpm  |
| Oil Lubrication – T Seal            | 2900 rpm  |
| Oil Lubrication – B/C/O Seal        | 1300 rpm  |
| Grease Lubrication – M/N Seal       | 1600 rpm  |
| Grease Lubrication – T Seal         | 2400 rpm  |
| Grease Lubrication – B/C/O Seal     | 1300 rpm  |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0030    |
| Eng Internal Radial Clearance – Max | 0.0037    |
| Pre Install Clearance Min           | 0.0030 in |
| Pre Install Clearance Max           | 0.0037 in |