

Toyana TUP2 240.60 plain bearings

Request A Quote For Your Special Toyana TUP2 240.60 plain bearings Needs 57.15×25.4×18.875 Size (mm) Today! Free Quotes. ISO 9001 certified.

Size (mm)	57.15×25.4×18.875
Bore Diameter (mm)	57,15
Outer Diameter (mm)	25,4
Width (mm)	18,875
d	25.4 mm
D	57.15 mm
B	18.875 mm
d1	35.58 mm
D2	49.33 mm
r1,2 – min.	1.6 mm
da – min.	33 mm
Da – max.	50 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	17.8 kN
Basic static load rating – C0	9.6 kN
Fatigue load limit – Pu	0.405 kN
Reference speed	24000 r/min
Limiting speed	17000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	13
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0.179
EAN	7316577017680
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Inch
Long Description	1" Bore; 2-1/4" Outside Diameter; 5/8" Outer Race Width; Open; Ball Bearing; ABEC 1
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	RLS 8
Weight / LBS	0.395
Bore	1 Inch 25.4 Millimeter
Outside Diameter	2.25 Inch 57.15 Millimeter
Outer Race Width	0.625 Inch 15.875 Millimeter
bore diameter:	1.0000 in
static load capacity:	9.65 kN
outside diameter:	2.2500 in

precision rating:	Not Rated
overall width:	0.6250 in
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	15.875 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1.5 mm
internal clearance:	C0
maximum rpm:	17000 RPM
dynamic load capacity:	17.8 kN
series:	RLS
d1 ≈	35.58 mm
D2 ≈	49.33 mm
r1,2 min.	1.6 mm
da min.	33 mm
Da max.	50 mm
ra max.	1.5 mm
Basic dynamic load rating C	17.8 kN
Basic static load rating C0	9.65 kN
Fatigue load limit Pu	0.405 kN
Calculation factor kr	0.025
Calculation factor f0	13
Mass bearing	0.17 kg