

# UST206 SNR D1 40.3 mm Bearing units

|   |         |
|---|---------|
| A2  | 28 mm   |
| B   | 30 mm   |
| A5  | 22 mm   |
| G   | M6x1    |
| H2  | 56 mm   |
| N2  | 37 mm   |
| s1  | 15 mm   |
| S   | 8 mm    |
| SW  | 3 mm    |
| C   | 19.5 kN |
| C0  | 11.2 kN |
| T min.                                      | -20 °C  |
| T max.                                      | 100 °C  |
| Recommended tightening torque for set screw | 5.5 Nm  |
| Designation of housing                      | T206-   |
| Designation of bearing                      | US206G2 |
| Bearing number                              | UST206  |
| Brand                                       | SNR     |
| Bore Diameter (mm)                          | 30      |
| d   | 30 mm   |
| L4  | 57 mm   |
| L5  | 16 mm   |
| L2  | 10 mm   |
| L3  | 70 mm   |
| s   | 8 mm    |

|                               |         |
|-------------------------------|---------|
| A                             | 37 mm   |
| A1                            | 28 mm   |
| B1                            | 30 mm   |
| D1                            | 40.3 mm |
| H                             | 102 mm  |
| H1                            | 56 mm   |
| L                             | 113 mm  |
| L1                            | 41.5 mm |
| N                             | 22 mm   |
| N1                            | 37 mm   |
| Thread (G)                    | M6x1    |
| J1                            | 12 mm   |
| J2                            | 89 mm   |
| Weight                        | 1.2 Kg  |
| Basic dynamic load rating (C) | 19.5 kN |