

**WC87502 NTN Long Description
15MM Bore; 35MM Outside
Diameter; 12.7MM Outer Race
Width; 1 Seal-1 Metal Shield;
Ball Bearing; ABEC 1 | ISO
P0; No Filling Slot; No Snap
Ring; Smaller Inner Ring
Internal Special Features;
C0-Medium Internal Clearance;
12.2MM Inner Race Width
15x35x12.700mm Deep groove
ball bearings**

Bearing number	WC87502
Size (mm)	15x35x12.700
Brand	NTN
Bore Diameter (mm)	15.000
Outer Diameter (mm)	35.000
Width (mm)	12.700
d	15.000 mm
D	35.000 mm
B	12.700 mm
C	12.700 mm

Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359601978
Product Group – BDI	B00234
Enclosure	1 Seal-1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Smaller Inner Ring
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 12.7MM Outer Race Width; 1 Seal-1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Smaller Inner Ring Internal Special Features; C0-Medium Internal Clearance; 12.2MM Inner Race Width
Other Features	Deep Groove Felt Seal Shell Alvania Prelubricated
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68

Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.12
Outside Diameter	1.378 Inch 35 Millimeter
Bore	0.591 Inch 15 Millimeter
Outer Race Width	0.5 Inch 12.7 Millimeter
Inner Race Width	0.48 Inch 12.2 Millimeter
bore diameter:	15 mm
static load capacity:	3600 N
outside diameter:	35 mm
precision rating:	ISO Class 0
overall width:	12.7 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	One Seal/One Shield
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	12.192 mm
snap ring included:	Without Snap Ring
outer ring width:	12.700 mm
internal clearance:	CN
maximum rpm (grease):	15000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	0.6 mm
dynamic load capacity:	7750 N

manufacturer product
page:

[Click here](#)