

# ZEN 6209-2Z deep groove ball bearings

Enjoy High 35 Bore Diameter (mm) Margins on Competitive Pricing.Great 35x35x17 Size (mm) Wholesale Products at Low Costs.

|                               |            |
|-------------------------------|------------|
| Size (mm)                     | 35x35x17   |
| Bore Diameter (mm)            | 35         |
| Outer Diameter (mm)           | 35         |
| Width (mm)                    | 17         |
| d                             | 35 mm      |
| A                             | 35 mm      |
| A1                            | 17 mm      |
| A3 – H14                      | 3.2 mm     |
| A5                            | 22 mm      |
| B                             | 42.9 mm    |
| B4                            | 6 mm       |
| Da – H11                      | 88.9 mm    |
| Db                            | 90 mm      |
| J                             | 130 mm     |
| H                             | 14.8 mm    |
| L                             | 96 mm      |
| s1                            | 25.4 mm    |
| T                             | 46.4 mm    |
| Basic dynamic load rating – C | 25.5 kN    |
| Basic static load rating – C0 | 15.3 kN    |
| Fatigue load limit – Pu       | 0.655 kN   |
| Limiting speed                | 5300 r/min |

|                                                   |            |
|---------------------------------------------------|------------|
| Mass bearing unit                                 | 0.59 kg    |
| Thread – G2                                       | M6x0.75    |
| Hexagonal key size for grub screw – H             | 3 mm       |
| Inventory                                         | 0.0        |
| Manufacturer Name                                 | SKF        |
| Minimum Buy Quantity                              | N/A        |
| Weight / Kilogram                                 | 0          |
| Product Group                                     | M06110     |
| Housing material                                  | Composite  |
| Da                                                | 88.9 mm    |
| A3                                                | 3.2 mm     |
| N                                                 | 14.8 mm    |
| Basic dynamic load rating C                       | 25.5 kN    |
| Basic static load rating C0                       | 15.3 kN    |
| Fatigue load limit Pu                             | 0.655 kN   |
| Thread grub screw G2                              | M6x0.75    |
| Hexagonal key size for grub screw N               | 3 mm       |
| Recommended tightening torque for grub screw      | 4 N·m      |
| Recommended diameter for attachment bolts, mm G   | 12 mm      |
| Recommended diameter for attachment bolts, inch G | 0.5 in     |
| Housing                                           | FYTBK 507  |
| Bearing                                           | YAR 207-2F |
| End cover                                         | ECY 207    |