

ZEN P6204-SB deep groove ball bearings

Advance ZEN P6204-SB deep groove ball bearings is your source for 55 mm d quality and accessories. shop online for home delivery or pick up in one of 55 Bore Diameter (mm) our 10000 .

| | |
|-------------------------------|----------|
| Bore Diameter (mm) | 55 |
| d | 55 mm |
| Da | 125 mm |
| s1 | 33.4 mm |
| A1 | 15 mm |
| B | 55,6 mm |
| G | 16 mm |
| J | 150 mm |
| L | 185 mm |
| N | 19 mm |
| T | 46,4 mm |
| A2 | 15 mm |
| A3 | 12 mm |
| J1 | 106.1 mm |
| Weight | 4,3 Kg |
| Basic dynamic load rating (C) | 43,6 kN |
| Basic static load rating (C0) | 29 kN |
| Fatigue load limit (Pu) | 1,25 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |

| | |
|---|---------------|
| UNSPSC | 31171501 |
| Weight / Kilogram | 4.115 |
| EAN | 7316570872170 |
| Product Group | M06110 |
| Housing material | Cast iron |
| A | 43 mm |
| B4 | 9 mm |
| Db | 127.1 mm |
| RG | 1/4-28 UNF |
| R1 | 24.5 mm |
| DN | 6.5 mm |
| SWN | 7 mm |
| GN | 1/4-28 SAE-LT |
| Basic dynamic load rating C | 43.6 kN |
| Basic static load rating C0 | 29 kN |
| Fatigue load limit Pu | 1.25 kN |
| Limiting speed with shaft tolerance h6 | 3600 r/min |
| Mass unit | 3.95 kg |
| Thread grub screw G2 | M10x1 |
| Hexagonal key size for grub screw N | 5 mm |
| Recommended tightening torque for grub screw | 16.5 N·m |
| Recommended diameter for attachment bolts, mm G | 16 mm |
| Recommended diameter for attachment bolts, inch G | 0.625 in |
| Bearing | YAR 211-2F |
| Housing | FYC 511 |