ZEN S1200-2RS self aligning ball bearings

ZEN S1200-2RS self aligning ball bearings Needs 9 Days or more Days to Ship Analysis , Manufacturing Service 120 d . Get Your Free.

Days to Ship	9 Days or more
d	120
D	180
В	28
Precision (JIS)	Grade 0
Number of Raceway Ring Rows	Single Row
Specifications/Environment	Standard
Basic Load Rating, Dynamic Rating(N)	139000
Internal Clearance Symbol	CN (Normal Clearance)
Shaft Bore Config.	Cylindrical Bore
Format symbol	NU (double brims for the outer ring)
Holder Symbol	No
Specifications	Standard
Symbol of Bearing Ring Shape	No symbol: Internal diameter cylinder hole
Revolution Frequency(rpm)	3800
Outer ring oil hole	Standard
Large-capacity type	Standard
Combination of two pieces	Standard
Cylinder shape (suffix symbol: X)	No
Raceway Ring Shape	Cylindrical Roller

Load Direction	Radial
Inner/Outer Ring Material	Steel
Rolling Element Material	Steel
High-Speed Steel	Standard
RoHS	6
I.D.(Ø)	120
0.D.(Ø)	180
Width(mm)	28
Size Standards	Metric System
Outer Ring Type	Flat
Retainer Type	Momi removing
Rotational Speed(rpm)	3400
Basic Load Rating, Static Rating(N)	191000
Clearance sign	No
Accuracy(Class)	Class 0
Bearing Ring Type	Type NU
Acoustic Symbol	No
Seal, Shield Symbols	No
Precision Grade Symbol	No
Symbol of contact angle	No
Special Configurations Code	No
Symbols of Lubrication Amount	No
Internal Symbol	No
Outer Ring	With Outer Ring
Holder Color	No
Low Torque Specification	No
Material Symbol	No