

# ZEN S1640-2Z deep groove ball bearings

Enjoy High Margins on Competitive Pricing.Great 0.0 Inventory Wholesale Products at Low Costs.

|                                 |  |
|---------------------------------|--|
| Inventory                       | 0.0  |
| Manufacturer Name               | NTN  |
| Minimum Buy Quantity            | N/A  |
| Weight                          | 8.72   |
| EAN                             | 4547359295634  |
| Product Group                   | B00152   |
| Enclosure                       | Open   |
| Flush Ground                    | No   |
| Rolling Element                 | Ball Bearing   |
| Number of Rows of Balls         | Double Row   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | Yes  |
| Snap Ring                       | No   |
| Cage Material                   | Steel  |
| Contact Angle                   | 30 Degree  |
| Internal Clearance              | C3-Loose   |
| Number of Bearings              | 1 (Single)   |
| Inch – Metric                   | Metric   |
| Long Description                | 110MM Bore; 200MM Outside Diameter; 69.8MM Width; Open; No Flush Ground; Ball Bearing; Double Row of |
| UNSPSC                          | 31171531   |

|                               |                              |
|-------------------------------|------------------------------|
| Harmonized Tariff Code        | 8482.10.50.28                |
| Noun                          | Bearing                      |
| Keyword String                | Angular Contact              |
| Manufacturer Item Number      | 3222C3                       |
| Weight / LBS                  | 19.205                       |
| d                             | 4.331 Inch   110 Millimeter  |
| B                             | 2.748 Inch   69.8 Millimeter |
| D                             | 7.874 Inch   200 Millimeter  |
| bore diameter:                | 110 mm                       |
| radial dynamic load capacity: | 214000 N                     |
| outside diameter:             | 200 mm                       |
| radial static load capacity:  | 287000 N                     |
| overall width:                | 2.7500 in                    |
| operating temperature range:  | -40 to 120 °C                |
| contact angle:                | 30 °                         |
| cage material:                | Brass                        |
| row type & fill slot:         | Double-Row Non-Fill Slot     |
| finish/coating:               | Uncoated                     |
| bore type:                    | Round                        |
| precision rating:             | Class 0                      |
| closure type:                 | Open                         |
| fillet radius:                | 2.032 mm                     |
| snap ring included:           | Without Snap Ring            |
| weight:                       | 8.690 kg                     |
| bearing material:             | High Carbon Chrome Steel     |
| manufacturer product page:    | <a href="#">Click here</a>   |