

ZEN S2201 self aligning ball bearings

ZEN S2201 self aligning ball bearings Deal is your source for 17 mm d OEM and accessories. We 10 mm B sell 35 mm D Genuine at discount prices.

| | |
|---|------------|
| d | 17 mm |
| D | 35 mm |
| B | 10 mm |
| rs min | 0.3 mm |
| Radial clearance class | CN |
| Mass | 0.04 kg |
| Dynamic load, C | 6.8 kN |
| Static load, C ₀ | 3.35 kN |
| Fatigue limit load, C _u | 0.15 kN |
| f ₀ | 13.6 |
| N _{lim} (grease) | 14,000 rpm |
| Min operating temperature, T _{min} | -25 °C |
| Max operating temperature, T _{max} | 110 °C |
| Characteristic cage frequency, FTF | 0.39 Hz |
| Characteristic rolling element frequency, BSF | 4.47 Hz |
| Characteristic outer ring frequency, BPF ₀ | 3.14 Hz |
| Characteristic inner ring frequency, BPFI | 4.86 Hz |
| da min | 19 mm |
| da max | 21 mm |

| | |
|---------------------------------|--|
| Da max | 33 mm |
| ra max | 0.3 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.039 |
| Product Group | B00308 |
| Enclosure | 1 Seal |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 17MM Bore; 35MM Outside Diameter; 10MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No F |
| Other Features | Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.08598 |

| | |
|------------------|----------------------------|
| Bore | 0.669 Inch 17 Millimeter |
| Outer Race Width | 0.394 Inch 10 Millimeter |
| Outside Diameter | 1.378 Inch 35 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |