

# ZEN S602X-2Z deep groove ball bearings

ZEN S602X-2Z deep groove ball bearings manufacturer and global supplier ASAHI BEARINGS Manufacturer Name of reliable ball and roller ... ZEN S602X-2Z deep groove ball bearings Industries Products Manufacturing & Engineering and Agricultural 0.0 Inventory Bearings designed to meet the unique requirements of our targeted industries.

|                           |                     |
|---------------------------|---------------------|
| Inventory                 | 0.0                 |
| Manufacturer Name         | ASAHI BEARINGS      |
| Minimum Buy Quantity      | N/A                 |
| Weight                    | 0.98                |
| EAN                       | 0808250253081       |
| Product Group             | M06110              |
| Number of Mounting Holes  | 2                   |
| Mounting Method           | Set Screw           |
| Housing Style             | 2 Bolt Pillow Block |
| Rolling Element           | Ball Bearing        |
| Housing Material          | Thermoplastic       |
| Expansion / Non-expansion | Non-expansion       |
| Mounting Bolts            | 12 Millimeter       |
| Relubricatable            | Yes                 |
| Insert Part Number        | MUC208              |
| Seals                     | Contact Seal        |
| Housing Configuration     | 1 Piece Solid       |
| Inch – Metric             | Metric              |

|                               |  |
|-------------------------------|--|
| Other Features                | Single Row   Spherical   Normal Duty   Black Housing   Closed End   Has Slinger                      |
| Long Description              | 2 Bolt Pillow Block; 40MM Bore; 49.2MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubri |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | MUCPPL208CEB   |
| Weight / LBS                  | 2.15   |
| Nominal Bolt Center to Center | 5.4 Inch   136 Millimeter  |
| D                             | 1.937 Inch   49.2 Millimeter   |
| d                             | 1.575 Inch   40 Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter   |
| Actual Bolt Center to Center  | 5.4 Inch   136Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter   |
| B                             | 1.937 Inch   49.2 Millimeter   |