

ZEN S6308-2RS deep groove ball bearings

What are the types of ZEN S6308-2RS deep groove ball bearings ? Manufacturing Service . Get Your Free, Instant price, design review. 125.412 mm da 250 mm Da

da	125.412 mm
Da	250 mm
Ca	77.8 mm
A1	149.225 mm
A2	260.35 mm
S	4.763 mm
ba	61.119 mm
H	298.45 mm
H1	152.4 mm
H2	60.325 mm
J min.	406.4 mm
J max.	434.975 mm
J1	85.725 mm
L	511.175 mm
N1	28.575 mm
R1	87.313 mm
R2	38.1 mm
RG	3/4 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SAFS 528
Bearing	22228 CCK/W33

Adapter sleeve assembly	SNW 28×4.15/16
Stabilizing ring	SR-28-0
Taconite seal	TER 122
End plug (suffix Y)	EPR 27
Max. speed for Taconite seal	625 r/min
P60°	301 kN
P90°	180 kN
P120°	116 kN
P150°	105 kN
P180°	127 kN
Pa	28.5 kN
Mass pillow block	92.5 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	481.95 g