

ZKLF50115-2RS INA 50x115x34mm d1 72 mm Thrust ball bearings

| | |
|----------------------------------|-------------------------------|
| Bearing number | ZKLF50115-2RS |
| Size (mm) | 50x115x34 |
| Brand | INA |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 115 |
| Width (mm) | 34 |
| d | 50 mm |
| D | 115 mm |
| B | 34 mm |
| C | 34 mm |
| Screw | 6 |
| I | 25 mm |
| Angle (?) | 60 ° |
| b | 3 mm |
| d1 | 72 mm |
| d2 | 8.8 mm |
| r min. | 0.3 mm |
| r1 min. | 0.6 mm |
| J | 94 mm |
| Bolt (G) | M8 |
| Weight | 1.86 Kg |
| Basic dynamic load rating (C) | 46.5 kN |
| Basic static load rating (C0) | 126 kN |
| Category | Angular Contact Ball Bearings |

| | |
|---------------------------------|---|
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 2.227 |
| Product Group – BDI | B04270 |
| Enclosure | 2 Seals |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | Yes |
| Cage Material | Plastic |
| Contact Angle | 60 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Inch – Metric | Metric |
| Long Description | 50MM Bore; 115MM Outside Diameter; 34MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; C0-Medium; Plastic Cage; 60 Degree; 1 (Single) |
| Other Features | With Fixing Holes With Snap Ring Groove |
| Category – BDI | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |

| Keyword String | Angular Contact |
|------------------|---|
| Manufacturer URL | http://www.ina.com |
| Weight / LBS | 4.10059 |
| Outside Diameter | 4.528 Inch 115 Millimeter |
| Width | 1.339 Inch 34 Millimeter |
| Bore | 1.969 Inch 50 Millimeter |