

ZVL 32208A tapered roller bearings

ZVL 32208A tapered roller bearings Needs Analysis , Manufacturing Service . Get Your 8x24x8 Size (mm) Free.

Size (mm)	8x24x8
Bore Diameter (mm)	8
Outer Diameter (mm)	24
Width (mm)	8
d	8 mm
D	24 mm
B	8 mm
C	8 mm
d1	14,4 mm
d2	– mm
r1 min.	10,4 mm
r2 min.	10,4 mm
D1	21,2 mm
D2	0,3 mm
da min.	10.4 mm
Da max.	21.6 mm
ra max.	0.3 mm
Weight	0,018 Kg
Basic dynamic load rating (C)	3,9 kN
Basic static load rating (C0)	1,66 kN
Fatigue load limit (Pu)	0,071
Reference speed	63000 r/min
Limiting speed	32000 r/min

Calculation factor (f0)	13
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.02
EAN	7316572112403
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	8MM Bore; 24MM Outside Diameter; 8MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	628-2Z
Weight / LBS	0.018
Bore	0.315 Inch 8 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	0.945 Inch 24 Millimeter
d1 ≈	14.45 mm
D2 ≈	21.2 mm
r1,2 min.	0.3 mm
da max.	14.4 mm
Basic dynamic load rating C	3.9 kN
Basic static load rating C0	1.66 kN
Fatigue load limit Pu	0.071 kN
Calculation factor kr	0.025
Calculation factor f0	13
Mass bearing	0.018 kg