

ZVL K-M86649/K-M86610 tapered roller bearings

Various types and sizes 35 Bore Diameter (mm) to accommodate your ZVL K-M86649/K-M86610 tapered roller bearings 35x80x28 Size (mm) requirements.

Size (mm)	35x80x28
Bore Diameter (mm)	35
Outer Diameter (mm)	80
Width (mm)	28
D	80 mm
d	35 mm
C	28 mm
B	29 mm
d1	44 mm
r1,2 – min.	1.1 mm
r, r3,4 – min.	0.6 mm
Basic dynamic load rating – C	51.2 kN
Basic static load rating – C0	68 kN
Fatigue load limit – Pu	8.3 kN
Maximum static radial loads – Fr	57 kN
Maximum static radial loads – F0r	81.5 kN
Limiting speed	2000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.84
EAN	7316577728876

Product Group	B04120
Roller Surface Profile	Flat
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Cylindrical Roller Bearing – Double Row
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Full Complement With Flanged Inner Ring Labyrinth Seal
Long Description	35MM Bore; 80MM Roller Diameter; 28MM Roller Width; Flat Roller; Yoke Type; Sealed; Cylindrical Roll
UNSPSC	31171530
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NUTR 3580 X
Weight / LBS	1.852
Roller Diameter	3.15 Inch 80 Millimeter
Roller Width	1.102 Inch 28 Millimeter
Bore	1.378 Inch 35 Millimeter
r1,2 min.	1.1 mm
r, r3,4 min.	0.6 mm
Basic dynamic load rating C	51.2 kN
Basic static load rating C0	68 kN
Fatigue load limit Pu	8.3 kN

Maximum dynamic radial loads $F_{r \max}$.	57 kN
Maximum static radial loads $F_{0r \max}$.	81.5 kN
Mass support roller	0.84 kg