

# ZXY 7518EX tapered roller bearings

How 36.513 mm da do you find the ZXY 7518EX tapered roller bearings specification? Manufacturers 85.001 mm Da Online Free check

da	36.513 mm
Da	85.001 mm
Ca	28.804 mm
A1	60.325 mm
A2	153.988 mm
S	2.778 mm
ba	24.606 mm
H	112.713 mm
H1	57.15 mm
H2	20.637 mm
J min.	158.75 mm
J max.	177.8 mm
L	209.55 mm
N1	15.875 mm
R1	28.575 mm
R2	12.7 mm
RG	1/8 NPT
PG	1/8 NPT
h	24.606 mm
Housing	SAF 509
Bearing	22209 EK
Adapter sleeve assembly	SNW 9×1.7/16

Stabilizing ring	SR-9-9
Taconite seal	TER 17
End plug (suffix Y)	EPR 3
Max. speed for Taconite seal	2175 r/min
P60°	20.9 kN
P90°	12.5 kN
P120°	7.56 kN
P150°	6.67 kN
P180°	8.01 kN
Pa	3.09 kN
Mass pillow block	5.28 kg
Cap bolt	2 x 7/16-14 UNC
Cap bolt recommended tightening torque	61 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	25.515 g